



TL


BATTERY CHARGER

PBM *Group*

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

pbmbatterychargers.com

P.B.M. Srl
Via Barella Z.I.
41058 Vignola (Modena) ITALY

 +39 059 7705311

 info@gruppopbm.it



- ▶ Single phase charger 220/230/240VAC or 110VAC on request, Frequency 50-60HZ
- ▶ WA profile for charging time 10-12h
- ▶ Protection fuse on MAIN INPUT and DC OUTPUT
- ▶ Coated with Epoxy powder
- ▶ Equipped with power cord and charging cable

BATTERY CHARGER

MODEL

TL

Model	Ah Battery	
	10 ÷ 11 h	Mains
12V / 15A	90 ÷ 105	230
12V / 20A	110 ÷ 140	230
12V / 25A	150 ÷ 175	230
12V / 30A	180 ÷ 210	230
12V / 40A	220 ÷ 280	230
12V / 50A	300 ÷ 340	230
12V / 60A	350 ÷ 400	230
24V / 15A	90 ÷ 105	230
24V / 20A	110 ÷ 140	230
24V / 25A	150 ÷ 175	230
24V / 30A	180 ÷ 210	230
24V / 40A	220 ÷ 280	230
24V / 50A	300 ÷ 340	230
24V / 60A	350 ÷ 400	230
36V / 15A	90 ÷ 105	230
36V / 20A	110 ÷ 140	230
36V / 25A	150 ÷ 175	230
36V / 30A	180 ÷ 210	230
36V / 40A	220 ÷ 280	230
36V / 50A	300 ÷ 340	230
48V / 20A	110 ÷ 140	230
48V / 30A	180 ÷ 210	230